

Hawk 216 EMCCD

Ultra Sensitive Monochrome EMCCD camera
768 x 576 • 25/30Hz • Analog



Key Features and Benefits

Cooled VGA Surveillance UV EMCCD

- **Back Illuminated EMCCD technology**
Enables ultimate sensitivity imaging (<math><50\mu\text{lux}</math>)
- **High QE: >90% @ 600nm**
GEN III image intensifier performance
- **Enhanced blue response from 180nm**
Low light UV with visible detection
- **Fan-less cooling**
Ideal for integration and discrete low light surveillance

Resolution	768 x 576
Frame Rate	25/30Hz
Dynamic Range	55dB
Peak QE	90% @ 500nm

Specification for Hawk 216 EMCCD

Sensor Type	2/3" Full frame transfer	
	CCIR	EIA
Active Pixel	769 x 288	769 x 244
Frame Rate	25Hz	30Hz
Pixel Size	11.5µm x 23µm	11.5µm x 27µm
Active Area	8.832 mm x 6.624 mm	8.832 mm x 6.588mm
Iris Control	Video / DC	
Dynamic Range	55dB	
Anti-blooming	Standard	
Spectral Response	180-1100nm	
Total Power Consumption	<8W	
Minimum Illumination	< 50µlux	
Video Connector	SMA type	
Resolution	625lines	525 TV lines
Readout mode	Interlaced	
Cooling	Active, no fan	
Lens Mount	C mount, Back focus capability	
Output Format	1.0Vp-p, 75Ω, ECIR or EIA	
Power Connector	9 pin Micro-D connector	
Power Supply	12V DC ±10%	
Operating Temperature Range	-20°C to +55°C	
Storage Temperature Range	-40°C to +70°C	
Dimensions	50mm x 45mm x 75mm (including CS-mount)	
Weight (excluding lens)	<230g	
Raptor Photonics Limited reserves the right to change this document at any time without notice and disclaims liability for editorial, pictorial or typographical errors.		

Ordering Information

Camera

Hawk EM216 Analog camera - CCIR	HK216-AP
Hawk EM216 Analog camera - EIA	HK216-AN

Optional Accessories

EPIX(R) base notebook CL card	RPL-EPIX-ECB1-34
EPIX(R) base notebook CL card	RPL-EPIX-ECB1-54
Hawk PSU cable MDM to flying leads	RPL-NDN-CBL-B
Hawk PSU cable MDM to Jack + brick	RPL-MDM-CBL-J
EPIX(R) Analogue video card	RPL-EPIX-SV5


Lenses

Optical Visible & CCTV day/night lenses	RPL-xx-xxxx
---	-------------

Demo is available on request.
Pricing AOR subject to volumes.

Detailed technical drawings
can be downloaded at
www.raptorphotonics.com

Quantum Efficiency



Applications

- Ground Based Surveillance
- Airborne Surveillance
- UV Imaging Blue Response
- Scientific Imaging
- Situational Awareness

Document #: INHK216 0318R1



Willowbank Business Park
Larne, Co Antrim
BT40 2SF,
Northern Ireland

ROW Sales
T: +44(0)2828 270 141
E: sales@raptorphotonics.com
www.raptorphotonics.com

USA Sales
T: (770) 364-7240
E: request@phxatl.com
www.phxatl.com

