

SLIP RING COLLECTOR TX4741 series

+ EX Slip Ring

Explosion Protected Group IIB Zone 1

Ex d IP66 - Stainless Steel Enclosure

Fibre Optic Rotary Joint Option

Applications include Cranes, Cable

Reels and Winches

OPTIONS

- Multi-pass Fibre Optic Rotary Joint
- Trolex Gas / Fluid Swivel
- Anti-condensation heater

CABLE ENTRY OPTIONS

The unit is supplied with factory fitted leads - the following options are available:

- Flying leads through a compound filled stopper box threaded to receive a suitable conduit
- Multi-core cable with appropriate cable gland
- Trolex Ex d multi-pin connector
- Trolex Ex d or Ex e junction box

OPERATING SPECIFICATIONS

Ambient Temperature Range	-20°C to +45°C (increased range available)
Maximum Speed	50 rpm (higher on request)
Maximum Voltage	4500 V ac
Current Rating	Max. 40 Amps per ring (may be used in parallel). Up to 136 rings subject to total throughput of 400 Amps excluding earths, screens and neutrals

TECHNICAL DETAILS

External Material	316L Stainless Steel
Bearings	Sealed for life, ball journal
Slip Rings	Phosphor bronze (precious metal plated for signals)
Brushes	Minimum of 2/ring (copper graphite for power, silver graphite for signals)
Fasteners	Stainless Steel Metric

APPROVAL CERTIFICATION

ATEX-standard	CML 16ATEX1399X EX II 2 G Ex db IIB T5 Gb Tamb -20°C to +40°C
ATEX Utilising the FORJ	CML 16ATEX1399X EX II 2 G Ex db op is IIB T5 Gb Tamb -20°C to +40°C
IECEX-standard	IECEX CML 16.0152X Ex d IIB T5 Gb Tamb -20°C to +40°C
IECEX Utilising the FORJ	IECEX CML 16.0152X Ex d op is IIB T5 Gb Tamb -20°C to +40°C

